



# Inspection Report Self Retracting Lanyards

## General Instructions

Perform the inspection of your equipment (review manufacturer’s instructions).

If a piece of equipment is acceptable for service enter “yes” or a check mark in the box for the applicable day of the week and initial in the adjacent box.

Workers who have a concern with a piece of equipment shall review the problem with their foreman. If there are any defects that would compromise the integrity of the equipment it must be repaired before use.

## Inspection Instructions – Fall Arrest Equipment

- Anchor Shackle:** Inspect the anchor shackle (at the top of the SRL) for signs of damage or corrosion.
- Load Indicator:** Verify the load indicator is not activated. Any SRL that has been involved in a fall incident shall not be used.
- Housing, Cover and Nozzle:** Inspect the housing, cover and nozzle for signs of damage.
- Operation:** Test the operation of the SRL. Does it lock if pulled quickly?
- Snap Hook:** Check for signs of defects. Verify the self-locking mechanism is functioning.
- Nylon Web:** Check all webbing for any signs of cuts, excessive fraying, piercing, pulled or broken stitching, abrasion, excessive wear, altered or missing straps, burns and heat or chemical exposure.

Worker’s Name: \_\_\_\_\_

Signature: \_\_\_\_\_

Date / Week of: \_\_\_\_\_

DAY OF WEEK	INITIALS, INSPECTION COMPLETE
Sunday	_____
Monday	_____
Tuesday	_____
Wednesday	_____
Thursday	_____
Friday	_____
Saturday	_____